

**PRODUCT SPEC SHEET**  
ZEBRA 8585 / 8595



**SoluTechnic Adis Ouest**  
BP10 Parc d'Activités  
49230 St Germain/Moine  
Tél: 02.41.49.18.30



Fax: 02.41.49.18.39 e.mail: [contact@stao-eu.fr](mailto:contact@stao-eu.fr) Site: [www.stao-eu.fr](http://www.stao-eu.fr)  
Imprimantes - Accessoires - Maintenance - Têtes d'impression  
Rubans Transfert - Etiquettes - Terminaux - Lecteurs



**ZEBRA**



## ZEBRA 8585 / 8595

### VEHICLE MOUNT COMPUTERS

The 8585 and 8595 are the latest rugged vehicle mount computers designed and built for the tough demands of such environments as warehouses, ports, manufacturing plants and airports.

These rugged vehicle mount computers are compact and still provide full PC functionality with a Windows® XP or Windows® 7 operating system. Thus, the 8585 and 8595 ensure your workers are equipped with the tools they need to get the job done efficiently and effectively.

#### COMPACT DESIGN

The 8585 and 8595 take up very little space. Their thin design makes it simple to mount wherever space is available in your vehicle. Once mounted, the compact dimensions of the 8585 and 8595 ensure your workers have access to their computer when needed without it getting in the way while performing other tasks.

#### THE LATEST IN MOBILE TECHNOLOGY

Built with the Intel Atom® Single Core processor or the AMD Dual Core processor, the 8585 and 8595 consume minimal power, but still operate quickly due to their 1.x GHz processor speed.

#### FAST AND RELIABLE COMMUNICATION

#### WHERE IS THE 8585/ 8595 AT HOME?

##### Industries

- 'ç Manufacturing
- 'ç Ports & Yards
- 'ç Airports
- 'ç Warehouses

Even in demanding WLAN networks, the 8585 and 8595 ensure that you are always connected with the rest of the team. Featuring an integrated diversity-antenna space diversity and 802.11 a/b/g/n WLAN, the 8585 and 8595 provide reliable communication and fast throughput.

### **EXTREME RUGGEDNESS**

The 8585 and 8595 have been tested on strict Standards for shock and vibration. Their IP66 rating means they are protected against vibration, dust and other impacts. Whether mounted to non-suspension vehicles or machines with substantial imbalances, the 8585 and 8595 will keep providing workers the support they need.

## **VEHICLE MOUNT INTELLIGENCE FOR RUGGED ENVIRONMENTS**

---



**SoluTechnic Adis Ouest**  
**BP10 Parc d'Activités**  
**49230 St Germain/Moine**  
Tél: 02.41.49.18.30



Fax: 02.41.49.18.39 e.mail: [contact@stao-eu.fr](mailto:contact@stao-eu.fr) Site: [www.stao-eu.fr](http://www.stao-eu.fr)

Imprimantes - Accessoires - Maintenance - Têtes d'impression  
Rubans Transfert - Etiquettes - Terminaux - Lecteurs

# TECHNICAL SPECIFICATIONS

PHYSICAL CHARACTERISTICS		USER ENVIRONMENT	
<b>Dimensions</b>	8585: 9.1 in. L x 11.2 in. H x 3.1 in. D (229 mm L x 285 mm H x 78 mm D) 8595: 10.1 in. L x 12.8 in. H x 3.1 in. D (258 mm L x 325 mm H x 79 mm D)	<b>Operating Temp.</b>	-30°C to +50°C / -22°F to +122°F
<b>Weight</b>	8585: 6.6 lb / 3 kg 8595: 7.7 lb / 3.5 kg	<b>Storage Temp.</b>	-35°C to +65°C / -31°F to +149°F
<b>Keyboard Options</b>	Multiple keyboards including the color option with 72 keys and the 82-key option with integrated backlighting	<b>Humidity</b>	10% to 90% at 40°, non-condensing
<b>Power</b>	12-24 VDC or 24-48 VDC internal power supply; Voltage sags up to 5 VDC can be handled for up to 20 seconds	<b>Sealing</b>	IP66; IP67
<b>Display</b>	8585: 10.4 in. diagonal SVGA (800 x 600); LED Backlight; Resistive touch screen; Sunlight Readability Option 8595: 12.1 in. diagonal XGA (1024 x 768); LED Backlight; Resistive touch screen	<b>Shock / Vibration</b>	Class 5M3 according EN 60721-3-5
<b>Audio / Voice System</b>	Integrated speaker; Speaker/Mic via handset (Optional)	<b>UV</b>	Per MIL-STD 810F (US Highway Truck)
<b>Interfaces</b>	1x RS-232; 2x USB 2.0 host; 1x Service USB 2.0; 1x Speaker/Mic; LAN: RJ45 10/100/1000 Mbps	<b>WIRELESS DATA COMMUNICATIONS</b>	
<b>Mounting</b>	Quick release mount; standard RAM mounts; adapters for legacy mounts; heavy duty mount; cantilever mount	<b>WLAN</b>	802.11a/b/g/n; PCIe MiniCard
<b>Indicators</b>	Power On LED; Temperature warning; Mass Storage Activity	<b>REGULATORY</b>	
<b>PERFORMANCE CHARACTERISTICS</b>		FCC Part 15 Subpart B, Class B, Emissions; Industry Canada ICES-003 Class B; EN 55022:1998, Class B, Emissions; EN 55024:1998 Immunity; EN 60950-1, UL 60950-1, CSA 22.2 No. 60950-1, Safety; ISO7637-1/2 Vehicle transients	
<b>CPU</b>	Intel Atom® (Single Core) 1.1 GHz; AMD G-T40E (Dual Core) 1.0 GHz	<b>ACCESSORIES</b>	
<b>Operating System</b>	Windows® XP Embedded; Windows® XP Professional; Windows®	For a full list of accessories, visit <a href="http://www.zebra.com/8585">www.zebra.com/8585</a> or <a href="http://www.zebra.com/8595">www.zebra.com/8595</a> .	
		<b>WARRANTY</b>	
		Subject to the terms of Zebra's hardware warranty statement, the 8585-8595 Vehicle Mount Computers are warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For complete warranty statement, go to: <a href="http://www.zebra.com/warranty">http://www.zebra.com/warranty</a>	
		<b>SERVICES AND SUPPORT</b>	
		- Zebra EMC Services	

Embedded Standard 7;  
Windows® Professional

---

**Memory**

Starting at 4 GB CFast Flash  
ROM; Up to 16 GB CFast  
Flash ROM; 1 GB RAM with  
Intel; 2GB RAM with AMD



**ZEBRA**

Part number: SS-8585/8595. Printed in USA 4/15.©2015 ZIH Corp. ZEBRA, the Zebra head graphic and Zebra Technologies logo are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All rights reserved. All other trademarks are the property of their respective owners.

---

**ZEBRA TECHNOLOGIES**



**SoluTechnic Adis Ouest**  
**BP10 Parc d'Activités**  
**49230 St Germain/Moine**  
Tél: 02.41.49.18.30



Fax: 02.41.49.18.39 e.mail: [contact@stao-eu.fr](mailto:contact@stao-eu.fr) Site: [www.stao-eu.fr](http://www.stao-eu.fr)

Imprimantes - Accessoires - Maintenance - Têtes d'impression  
Rubans Transfert - Etiquettes - Terminaux - Lecteurs